



RDL8500 Remote Data Logger

The RDL8500 remote data logger is installed at a submetering site's head end location to collect data from transmitters using the EN4000, EN6540 and/or FA403 RF gateways. The RDL8500 can remotely communicate with the billing service or with an onsite technician using the TapWatch.com website or the Inovonics TapWatch 3 software.

Product Features

- Provides reliable data collection for gas, water, electric and run-time meters
- Logs data for up to 2000 individually managed meters
- Stores 90 periods worth of meter reads per individual meter
- Time stamps incoming data
- LAN (RJ45) connection for direct PC connection
- WAN (RJ45) Ethernet for connecting, via the Internet, to TapWatch.com and a PC running TapWatch 3 software
- Analog phone line for remote communication via modem

Product Specifications

- Dimensions: 11.5" x 8.75" x 2.25" (29.2 cm x 22.2 cm x 5.7 cm)
- Weight: 2 lbs 7 oz (1.1 kg)
- Power requirement: 120 VAC; transformer included
- Operating environment:
 - Temperature: 32 to 130°F (0 to 54.4° C)
 - Humidity: Up to 90% (non-condensing)
- System requirements:
 - EN4000, EN6540 or FA403 receiver
 - Analog phone line
 - TapWatch 3 software
 - Ethernet broadband Internet connection for TapWatch.com
- Regulatory compliance: FCC, RoHS

Reference Materials (available at www.inovonics.com)

RDL8500 Remote Data Logger Installation Instructions

- The range and performance of any wireless product depends on the structure and environment in which it operates.
- Continual enhancements to our products may cause specifications to change without notice.
- Visit www.inovonics.com for UL information.
- Patent pending.