



EN1223S-60 Single-Button Water-Resistant Pendant Transmitter

The EN1223S-60 single-button water-resistant pendant transmitter features single-button, press-and-hold activation for ease of operation. Weighing 1.3 oz. with the battery installed, it comes with a neck cord and belt clip (wristband available for purchase) and can be easily converted by the end user.

Product Features

Can be worn in the shower, bathtub or rain

Fully supervised to help ensure reliability

Product Specifications

Dimensions: 2.2" x 1.9" x 0.72" (5.6 cm x 4.8 cm x 1.8 cm)

Weight: 1.3 oz (37 g)

Typical battery life: 1 – 2 years

Internal battery type: Panasonic CR2450

Operating environment:

Temperature: 32°F to 140°F (0°C to 60°C)

Environment: Water resistant, non-submersible

Market: North America

EchoStream® frequency: 902-928 MHz, frequency hopping spread spectrum

Check-in time frequency: 60 minutes

Regulatory compliance: FCC, RoHS, UL 2560¹, IP54 Dust and Water Resistance (IEC 60529)

Reference Materials (available at www.inovonics.com)

EN1223S/EN1223S-60 EchoStream® Single-Button Water-Resistant Pendant Transmitter Installation and Operation Manual

- The range and performance of any wireless product depends on the structure and environment in which it operates.
- Continual enhancements to our products may cause specifications to change without notice.
- Patents: 7,154,866; 7,554,932; 7,746,804; others pending.

¹ Partners must achieve emergency call system certification from a nationally recognized testing laboratory to claim compliance with UL 2560.