



EN1210-240 Single Input Universal Transmitter

Designed for use with any standard normally open or normally closed contact, the EN1210-240 single input universal transmitter is fully supervised and includes case tamper and battery.

Product Features

Mounting bracket included for quick and easy installation

Can be used with almost any standard NO/NC contact

Fully supervised

Includes case tamper protection

Product Specifications

Dimensions: 3.5" x 1.7" x 0.9"

Weight: 1.9 oz

Typical battery life: 3 – 5 years

Internal battery type: Panasonic CR123A

External contacts: Normally open or normally closed

Distance, external contact to EN1210: 10 feet

Operating environment:

Temperature: -4 to 140°F using internal battery

Humidity: Up to 90% (non-condensing)

Market: North America

EchoStream® frequency: 902-928 MHz, frequency hopping spread spectrum

Check-in time frequency: 240 minutes

Regulatory compliance: FCC, RoHS, UL 2560¹

Reference Materials (available at www.inovonics.com)

EN1210/EN1210-60/EN1210-240 EchoStream® Single Input Universal Transmitter Installation Instructions

Security End Device Developer Guide

EchoStream One-Way Security Developer Guide

- The range and performance of any wireless product depends on the structure and environment in which it operates.
- Continual enhancements to our products may cause specifications to change without notice.
- Patents: 7,154,866; 7,554,932; 7,746,804; others pending.

¹ Partners must achieve emergency call system certification from a nationally recognized testing laboratory to claim compliance with UL 2560. The EN1210-240 single input universal transmitter is a supplemental device that is allowed for use in a UL 2560 certified system, but does not carry the UL 2560 unlisted component certification.