



## EN1210W-60 Door/Window Transmitter with Reed Switch

The EN1210W-60 door/window transmitter with reed switch includes a built-in, side mounted magnetic reed switch, with a magnet that supports a 5/8" gap.

### Product Features

- Contains wired input and magnetic reed switch input
- Mounting bracket included for quick and easy installation
- Fully supervised
- Includes case tamper protection

### Product Specifications

Dimensions:	3.5" x 1.7" x 0.9"
Weight:	1.9 oz
Typical battery life:	3 - 5 years
Internal battery type:	Panasonic CR123A
External contacts:	Normally open or normally closed
Distance, external contact to EN1210W:	10 feet
Operating environment:	
Temperature:	-4 to 140°F using internal battery
Humidity:	Up to 90% (non-condensing)
Market:	North America
EchoStream® frequency:	902-928 MHz, frequency hopping spread spectrum
Check-in time frequency:	60 minutes
Regulatory compliance:	FCC, RoHS, UL 2560 <sup>1</sup>

### Reference Materials (available at [www.inovonics.com](http://www.inovonics.com))

EN1210W/EN1210W-60 EchoStream® Door/Window Transmitter with Reed Switch Installation Instructions

Security End Device Developer Guide

EchoStream One-Way Security Developer Guide

- The range and performance of any wireless product depends on the structure and environment in which it operates.
- Continual enhancements to our products may cause specifications to change without notice.
- Patents: 7,154,866; 7,554,932; 7,746,804; others pending.

<sup>1</sup> Partners must achieve emergency call system certification from a nationally recognized testing laboratory to claim compliance with UL 2560. The EN1210W-60 door/window transmitter with reed switch is a supplemental device that is allowed for use in a UL 2560 certified system, but does not carry the UL 2560 unlisted component certification.