



EN1212-60 Dual Input Universal Transmitter

The EN1212-60 dual input universal transmitter is designed for use with almost any standard contact or sensor and provides two inputs.

Product Features

Supports dual inputs

Can be used with almost any standard NO/NC contact

Fully supervised

Includes case tamper protection

Product Specifications

Dimensions: 3.5" x 1.7" x 0.9"

Weight: 1.9 oz

Typical battery life: 3 – 5 years

Internal battery type: Panasonic CR123A

External contacts: Normally open or normally closed

Distance, external contact to EN1212: 10 feet

Operating environment:

Temperature: -4 to 140°F using internal battery

Humidity: Up to 90% (non-condensing)

Market: North America

EchoStream® frequency: 902-928 MHz, frequency hopping spread spectrum

Check-in time frequency: 60 minutes

Regulatory compliance: FCC, RoHS, UL 2560¹

Reference Materials (available at www.inovonics.com)

EN1212/EN1212-60 Dual Input Universal Transmitter Installation Instructions

Security End Device Developer Guide

EchoStream One-Way Security Developer Guide

- The range and performance of any wireless product depends on the structure and environment in which it operates.
- Continual enhancements to our products may cause specifications to change without notice.
- Patents: 7,154,866; 7,554,932; 7,746,804; others pending.

¹ Partners must achieve emergency call system certification from a nationally recognized testing laboratory to claim compliance with UL 2560. The EN1212-60 dual input universal transmitter is a supplemental device that is allowed for use in a UL 2560 certified system, but does not carry the UL 2560 unlisted component certification.