


Inovonics Wireless Solutions

Inovonics' line of EchoStream® wireless intrusion detection devices and mobile duress (panic) buttons are designed with today's applications in mind. Supporting installations with thousands of security devices across a campus, the EchoStream family of pendant transmitters, universal transmitters, motion detectors and add-on receivers can connect to virtually any security system.

Unique to Inovonics is the high power repeater mesh that intelligently amplifies transmissions from EchoStream transmitters. Providing coverage in all types of building construction, thus eliminating the need for labor associated with wired installs. EchoStream provides the flexibility to cover small, medium and large commercial buildings as well as complete campuses.



Security Panel Partners

Inovonics offers direct integration to various panel partners along with add-on receivers that integrate with nearly any security system.

Compliance Specifications

Inovonics EchoStream products are configured to the appropriate country frequency and comply with applicable ACMA technical standards for telecommunications, short-range radio equipment, and EMC (Electromagnetic Compatibility). All Inovonics' security products in Australia and New Zealand have a C-Tick or RCM mark.




Commercial Panel Integration Options

Inovonics offers direct integration via serial receivers or add-on receivers.

Direct to Panel Integrations

Please contact your distribution partner for more information.

Add On Receivers

Receiver	Transmitters	Outputs	
		Alarm	Fault
EN4204R 	4	4	1
EN4216MR 	16	5	1*
EN4232MR 	32	11	1*

*User assigned fault outputs


Security System Configuration



Security Panel



Add-On or Serial Receiver



Repeater Network



Wireless Transmitters

 = Wired Connection

 = Wireless Connection

Water Resistant Pendant Transmitters

Compact single or double button pendant that can be supervised. LED flashes when transmitting. Ideal for healthcare applications.

Single Button **EN1223S**

Double Button **EN1223D**

Wristband **ACC623**



Necklace Pendant Transmitters

Sleek single or double button pendant that can be supervised. LED flashes when transmitting. Easy to wear with included necklace.

Single Button **EN1233S**

Double Button **EN1233D**



Belt Clip Pendant Transmitters

Sleek single or double button pendant that can be supervised. LED flashes when transmitting. Durable belt clip included.

Single Button **EN1235S**

Double Button **EN1235D**



Fixed Position Hold Up Pendant Transmitters

Fixed position transmitters include mounting hardware for easy installation and back tamper for removal alarms.

Single Button **EN1235SF**

Double Button **EN1235DF**




Four Condition Pendant Transmitters

Multiple condition pendants require the use of a multi-condition receiver and application designed to support advanced functionality.

Four Condition **EN1224**

Four Condition On/Off **EN1224-ON**




Multi Condition Pendant Transmitters

Multiple condition pendants require the use of a multi-condition receiver and application designed to support advanced functionality.

Three Condition **EN1236D**


Two Condition **EN1238D**



Universal Transmitters

Universal transmitters can be used with any standard N/O or N/C sensor and include a case tamper switch.

Universal Transmitter **EN1210**
With EOL Resistor **EN1210EOL**
Door/Window Transmitter with Reed Switch **EN1210W**



Universal Transmitters with Wall Tamper

Wall tamper switch adds protection from device removal.


Universal Transmitter with Wall Tamper **EN1215EOL**
With Reed Switch and Magnet **EN1215WEOL**



Dual Input Universal Transmitter

Dual input universal transmitters can be used with any standard N/O or N/C sensor and include an additional N/C input.

Dual Input Universal Transmitter **EN1212**
With Wall Tamper **EN1216**
Long Range **EN1252**



Smoke Detector


The **EN1244A** and **EN1244Z** feature an onboard sounder, an LED indicator, tamper, EchoStream® network supervision, and local test capability.

Smoke Detector **EN1244A (AU)**
EN1244Z (NZ)



Billtrap Transmitter

The **EN1249** provides the flexibility for use in cash drawers for use in any financial or retail environment. Features case and back tamper, Smart Baiting with LED confirmation, and two or ten second delay transmission modes.



Glassbreak Detector


The **EN1247** uses acoustic pattern recognition technology for proven performance, extended range, and increased immunity to false alarms. 6.1m radius allows for multiple window coverage.



360° Ceiling Mount Motion Detector

The **EN1265** four element motion detector offers a 360° coverage pattern, case tamper switch, and up to an 5.5m mounting height with the included lens.


High Ceiling Lens (7.62m) **ACC669**



360° Ceiling Mount Motion Detector Coverage

Top View

Side View



Motion Detector with Pet Immunity


The **EN1262** is designed for low traffic applications and features pet immunity to reduce false alarms from animals. Includes a case tamper switch and optional wall tamper.



Motion Detector with Pet Immunity Coverage

Top View

Side View



High Traffic Four Element Motion Detector

The **EN1261HT** is developed specifically for high traffic environments, delivering approximately four years of battery life. Includes case and back tamper, and features pet immunity up to 15kg/0.3m


Long Range Lens (18.3m) **ACC668**



High Traffic Four Element Motion Detector Coverage

Top View

Side View



Wall Mount Motion Detector

The **EN1260** features digital signal processing that recognizes human signatures to reduce false alarms.


Curtain Lens Kit **ACC672CT**
Long Range Lens Kit (30m) Kit (30m) **ACC672LR**
Pet Alley Lens Kit **ACC672PA**



Wall Mount Motion Detector Coverage

Top View


Side View



Add-On Receivers

Add-on receivers cost effectively add EchoStream wireless transmitters to any installation. Includes form C relays with dedicated alarm and fault output. The **EN4216MR** and **EN4232MR** are UL listed, support multi-condition transmitters, and include event logging.

Receiver	Transmitters	Outputs
EN4204R	4	4 Alarm / 1 Fault
EN4216MR	16	5 Alarm / 1 Fault
EN4232MR	32	11 Alarm / 1 Fault



Serial Receivers - Direct to Panel Integration

Serial receivers integrate directly to partner panels used in commercial access control/intrusion. These integrations leverage programming and wiring familiarity to expedite inclusion, or expansion, of wireless end points.

Please contact your distribution partner for more details.



High Power Repeater

The high power repeater **EN5040** amplifies transmissions from any transmitter.


Weatherproof Enclosure **ACC650**



Wireless Survey Kit

The **EN7016** wireless survey kit is a portable and easy to use tool for determining the optimal location for transmitters and repeaters. The wireless survey kit reduces bid risk, decreases installation time, and builds credibility with clients.

Includes both **EN1223SK** and **EN1210SK** survey transmitters



Survey Kit & App

The **EN7017** survey kit and app reduces bid risk, decreases installation time, and builds credibility with clients. Quickly prepare accurate quotes for even the most complex jobs.

Mobile app available on Android and iOS devices.

GET IT ON **Google Play** | Download on the **App Store**

