



The Inovonics billtrap transmitter features the same profile and ruggedness of a hard-wire billtrap, providing the flexibility necessary in any financial or retail environment.

### Product Features

- Two alarm transmission modes, two and ten-second delay, to reduce false alarms
- Wireless design provides ease of installation and drawer removal
- Case and back tamper
- Smart baiting feature provides LED confirmation when a bill has been inserted into the billtrap

### Product Specifications

Weight:	3.9 oz
Dimensions:	9.556" x 6.65" x 1.208"
Typical battery life:	3-4 years
Internal battery type:	Two Duracell DL123A
Operating environment:	
Temperature:	32°F to 140°F (0°C to 60°C)
Humidity:	Up to 90% (non-condensing)
Market:	North America
EchoStream® frequency:	902-928 MHz, frequency hopping spread spectrum
Check-in time frequency:	3 minutes
Regulatory compliance:	FCC, RoHS, UL

## Reference Materials (available at [www.inovonics.com](http://www.inovonics.com))

---

[EN1249 Billtrap Transmitter Installation Instructions](#)

---

[Inovonics Product Catalog: North America](#)

---

[EchoStream Developer Guide](#)

---

[EchoStream One-Way Security Developer Guide](#)

---

- The range and performance of any wireless product depends on the structure and environment in which it operates.
- Continual enhancements to our products may cause specifications to change without notice.
- Patents: 7,154,866; 7,554,932; 7,746,804; others pending.
- Inovonics supports recycling and reuse whenever possible. Please recycle these parts using a certified electronics recycler.

## Technical documents

---

For technical documents visit us at <http://www.inovonics.com/support/tech-documents/> or use the QR code below.

