



The security only serial receiver is a wireless gateway between EchoStream one-way security transmitters and a head end application using an RS-232 serial interface.

### Product Features

- Transmits EchoStream formatted messages to the head end application
- Supervises connection between the receiver and application
- Serial integration enables hundreds to thousands of wireless devices

### Product Specifications

Dimensions:	6.54" x 3.62" x 1.05" (166.1mm x 91.9mm x 26.67mm).
Weight:	5.1oz (145g)
Power requirement:	10-13.5 VDC at a minimum of 121mA
Operating environment:	
Temperature:	32° - 140°F
Environment:	90% relative humidity, non-condensing
Market:	North America, Australia, New Zealand
Frequency:	EchoStream® 902-928 MHz, frequency hopping spread spectrum
Regulatory compliance:	Security Level 1 CAN/ULC S304:2016, UL 985, UL 1023, UL 2610

## Reference Materials (available at [www.inovonics.com](http://www.inovonics.com))

---

EN4200 Security Only Serial Receiver Installation Instructions

---

EchoStream Developer Guide

---

Inovonics Product Catalog: North America

---

- The range and performance of any wireless product depends on the structure and environment in which it operates.
- Continual enhancements to our products may cause specifications to change without notice.
- Patents: 7,154,866; 7,554,932; 7,746,804; others pending.
- Inovonics supports recycling and reuse whenever possible. Please recycle these parts using a certified electronics recycler.

## Technical documents

---

For technical documents visit us at <http://www.inovonics.com/support/tech-documents/> or use the QR code below.

