



## TapWatch 3

The TapWatch 3 software communicates with the RDL8500 data logger and allows for configuring a submetered site, monitoring the performance of the submetering equipment, collecting site reads and generating reports. Remote communication with the data loggers at each site allows for efficient system management, and the integrated scheduler provides automated retrieval of meter reads.

### Product Features

---

Is able to communicate with RDL8500s using an IP connection, a modem, or the RDL8500's LAN (RJ45) connection

---

Configure site information, transmitters and repeaters

---

View RF signal strength from transmitters

---

Monitor RF messages received in real time

---

Automatically creates meter reads in a standard text file format

### TapWatch 3 Minimum System Requirements

---

PC with 1.2 gigahertz processor

---

Windows 7® or Windows 8.1®

---

1 GB RAM

---

4 GB of available hard disk space (additional space may be needed depending on site configuration)

---

Ethernet port

---

Available RS232 serial port and DB-9 connector or a USB port and an RS232 serial adapter

---

56k modem

---

Internet and IP connectivity

---

Video resolution of 1024x768

### TapWatch 3 Recommended System Requirements (assuming all other minimum requirements are met)

---

PC with 2 gigahertz processor

---

2 GB RAM

---

14 GB of available hard disk space

### Reference Materials (available at [www.inovonics.com](http://www.inovonics.com))

---

TapWatch 3 User Manual

• Continual enhancements to our products may cause specifications to change without notice.