



The Inovonics EN1235SF single-button fixed position hold up transmitter features a rugged design with simple, single-button activation, and a back tamper for tamper protection.

Product Features

Simple single-button activation

Includes back tamper for secure fixed position alarm signaling

LED flashes with all transmissions, ensuring operation at a glance

UL listed

Product Specifications

Dimensions: 3.0" x 1.6" x 0.72" (7.6 cm x 4 cm x 1.8 cm)

Weight: 1.6 oz (45 g)

Typical battery life: 3 to 5 years

Internal battery type: Panasonic CR2

Operating environment:

Temperature: 32°F to 140°F (0°C to 60°C)

Humidity: Up to 90% (non-condensing)

Market: North America, Australia, New Zealand

EchoStream® frequency: 902-928 MHz, frequency hopping spread spectrum

Check-in time frequency: 3 minutes

Regulatory compliance: FCC, RoHS, UL 365, UL 636, UL 1076, UL 1610

Reference Materials (available at www.inovonics.com)

EchoStream® EN1235SF/EN1235SF-15/EN1235DF Fixed Location Alarm Transmitter Installation Instructions

EchoStream Developer Guide

EchoStream One-Way Security Developer Guide

Inovonics Product Catalog: North America

- The range and performance of any wireless product depends on the structure and environment in which it operates.
- Continual enhancements to our products may cause specifications to change without notice.
- Patents: 7,154,866; 7,554,932; 7,746,804; others pending.
- Inovonics supports recycling and reuse whenever possible. Please recycle these parts using a certified electronics recycler.

Technical documents

For technical documents visit us at <http://www.inovonics.com/support/tech-documents/> or use the QR code below.

