



Multiple condition pendant transmitters

Through superior range and reliability, Inovonics EchoStream pendants offer virtually limitless opportunities for real world applications. Worn on a necklace, belt clip, wristband, or mounted in a fixed location, these lightweight, versatile pendants can be adapted to a wide range of installations.

All multiple condition pendant transmitters require the use of a serial receiver or network coordinator and application designed to support advanced functionality.

Why Inovonics Wireless is Best

The Inovonics Commercial Mesh Network has been specifically developed for commercial applications to provide the most cost-effective solution for a wide range of applications, while setting new standards for performance and reliability in a wireless sensor network.

Reliability

Inovonics EchoStream 900MHz radio utilizes a unique frequency hopping, spread spectrum technology to meet the demands of an increasingly cluttered wireless world.

Flexibility

The flexibility of wireless is a necessity in today's dynamic commercial environments. The self-configuring EchoStream Commercial Mesh Network allows you to adapt to changing floor plans and requirements in a matter of minutes. New sensors can be added to the network as fast as they can be mounted.

Scalability

The EchoStream Commercial Mesh Network's backbone of intelligent repeaters can extend coverage to thousands of sensors across entire commercial campuses.



EN1224 - Four button, multi-condition belt clip pendant

The EN1224 pendant is a four button, four condition transmitter. The EN1224-ON utilizes a 250 millisecond debounce time to activate conditions, and to help prevent false activation.



EN1224-ON - Four button, multi-condition belt clip pendant with on/off

The EN1224-ON pendant is a four button, four condition transmitter that includes both on and off buttons. The EN1224-ON utilizes a 250 millisecond debounce time to activate conditions, and to help prevent false activation.



EN1236D - Double-button, three condition, belt clip pendant

The EN1238D pendant is a two button device which can initiate three separate conditions. Pressing either button separately will activate the first two conditions, while pressing both buttons together will transmit the third condition.



EN1238D - Double-button, dual condition, belt clip pendant

The EN1238D pendant is a two button device which can initiate two separate conditions. Pressing either button separately will activate the first condition while pressing both buttons together will transmit the second condition.

Specifications					Pendant transmitter accessories	
Model	Frequency	Dimensions	Battery	Battery life	Part #	Description
EN1224	900MHz	3.0x1.6x1.0"	BAT608	3-5 years	ACC603L	Simulated leather neck cord
EN1224-ON	900MHz	3.0x1.6x1.0"	BAT608	3-5 years	ACC603M	Metal neck cord
EN1236D	900MHz	3.0x1.6x1.0"	BAT608	3-5 years	ACC603P	Plastic neck cord
EN1238D	900MHz	3.0x1.6x1.0"	BAT608	3-5 years	ACC605-BK	Pendant belt clip replacement

* Requires the use of a serial receiver or network coordinator and application designed to support advanced functionality.

- Operating Environment: 32° to 140°F, up to 90% relative humidity (non-condensing)
- Unless otherwise noted, typical battery life shown is for supervised operation
- Not all brands are equivalent. Please use only Sanyo or Panasonic CR2 or approved equivalent.
- The range and performance of any wireless product depends on the structure and environment in which it operates.
- Continual enhancements to our products may cause specifications to change without notice.
- Visit www.inovonics.com for updated UL information.