



The EN1224 is a four-button, multi-condition pendant transmitter.

### Product Features

---

Four-button design can be used to signal four conditions

---

Can be worn on a belt clip or mounted for fixed position signaling

---

LED flashes with all transmissions, ensuring operation at a glance

---

### Product Specifications

---

Dimensions: 3.0" x 1.6" x 0.72" (7.6 cm x 4 cm x 1.8 cm)

---

Weight: 2 oz (57 g)

---

Typical battery life: 3 to 5 years

---

Internal battery type: Panasonic CR2

---

Accessories: ACC605-BK10 pendant black belt clip, ten pack

---

Operating environment:

---

Temperature: 32°F to 140°F (0°C to 60°C)

---

Environment: Up to 90% (non-condensing)

---

Market: North America, Australia, New Zealand

---

Frequency: 902-928 MHz, frequency hopping spread spectrum

---

Check in time: 3 minutes

---

Regulatory compliance: FCC, RoHS

---

## Reference Materials (available at [www.inovonics.com](http://www.inovonics.com))

---

[EN1224 and EN1224-ON Installation Instructions](#)

---

[EchoStream Developer Guide](#)

---

[EchoStream One-Way Security Developer Guide](#)

---

[Inovonics Product Catalog: North America](#)

---

- The range and performance of any wireless product depends on the structure and environment in which it operates.
- Continual enhancements to our products may cause specifications to change without notice.
- Patents: 7,154,866; 7,554,932; 7,746,804; others pending.
- Inovonics supports recycling and reuse whenever possible. Please recycle these parts using a certified electronics recycler.

## Technical documents

---

For technical documents visit us at <http://www.inovonics.com/support/tech-documents/> or use the QR code below.

