



The EN1224-ON multiple condition on/off pendant is a four-button, multiple condition pendant transmitter, with the buttons configured for on/off applications.

Product Features

Buttons configured for on/off applications

Can be worn on a belt clip or mounted for fixed position signaling

LED flashes with all transmissions, ensuring operation at a glance

Product Specifications

Dimensions: 3.0" x 1.6" x 0.72" (7.6 cm x 4 cm x 1.8 cm)

Weight: 2 oz (57 g)

Typical battery life: 3 to 5 years

Internal battery type: Panasonic CR2

Accessories: ACC605-BK10 pendant black belt clip, ten pack

Operating environment:

Temperature: 32°F to 140°F (0°C to 60°C)

Environment: Up to 90% (non-condensing)

Market: North America, Australia, New Zealand

Frequency: 902-928 MHz, frequency hopping spread spectrum

Check in time: 3 minutes

Regulatory compliance: FCC, RoHS

Reference Materials (available at www.inovonics.com)

[EN1224 and EN1224-ON Installation Instructions](#)

[EchoStream Developer Guide](#)

[EchoStream One-Way Security Developer Guide](#)

[Inovonics Product Catalog: North America](#)

- The range and performance of any wireless product depends on the structure and environment in which it operates.
- Continual enhancements to our products may cause specifications to change without notice.
- Patents: 7,154,866; 7,554,932; 7,746,804; others pending.
- Inovonics supports recycling and reuse whenever possible. Please recycle these parts using a certified electronics recycler.

Technical documents

For technical documents visit us at <http://www.inovonics.com/support/tech-documents/> or use the QR code below.

