



When deployed as part of an Inovonics mobile duress or senior living system, EN5061 flush mount locators help determine precise floor and room location to improve response times.

### Product Features

Provides precise location for alarm events when used with Inovonics location-enabled pendants

Flush mount design decreases visibility and ensures tamper-free operation

24/7 monitoring to maintain system health

Works with existing Inovonics security and senior living systems, eliminating forklift upgrades

### Product Specifications

Dimensions:	5.50" x 5.50" x 1.01" (139.7 mm x 139.7 mm x 25.7 mm)
Weight:	4.8 oz. (136 g)
Power requirement:	12-24VAC 50/60 Hz or 12-24VDC; 670 mW
Operating environment:	
Temperature:	32 to 113°F (0 to 45°C)
Environment:	90% relative humidity, non-condensing
Market:	North America
Frequency:	EchoStream® 902-928 MHz, frequency hopping spread spectrum; 2.402 GHz to 2.480 GHz
Compatible gateways:	EN7295 mobile duress gateway; EN7380 senior living gateway
Check in time:	60 minutes
Regulatory compliance:	FCC Part 15, Subpart C, RSS-247 Issue 2, RoHS Directive 2015/86
UL certification:	UL and cUL Listed to UL 62368-1, audio/video, information and communication technology equipment

## Reference Materials (available at [www.inovonics.com](http://www.inovonics.com))

---

[EN5061 Flush Mount Locator Installation Instructions](#)

---

[Mobile Duress Brochure](#)

---

[Advanced Location Solution Brochure](#)

---

- The range and performance of any wireless product depends on the structure and environment in which it operates.
- Continual enhancements to our products may cause specifications to change without notice.
- Patents: 7,154,866; 7,554,932; 7,746,804; others pending.
- Inovonics supports recycling and reuse whenever possible. Please recycle these parts using a certified electronics recycler.

## Technical documents

---

For technical documents visit us at <http://www.inovonics.com/support/tech-documents/> or use the QR code below.

