



The Inovonics Intrusion System IDTOUCH1 touchpad connects to the Gateway Mark II hybrid panel for reliable performance and intuitive control. Featuring a sleek, high-resolution seven-inch full-color display, it allows users to easily arm, disarm, and bypass the system while providing realtime system status and alerts.

Product Features

Suitable for residential and commercial applications

Multi-language support (English, Spanish, French)

Thin low-profile design

Over-the-air firmware update capable

Product Specifications

Dimensions: 7.75" x 4.5" x 0.5"

Weight: 1 lb.

Power requirement: 18W

WiFi: Wi-Fi 6, WPA-2, 2.5 GHz and 5 GHz

Operating environment: 32°F (0°C) to 120°F (49°C); 0% to 85% relative humidity, non condensing

Storage environment: -40°F (-40°C) to 158°F (70°C); 0% to 85% relative humidity, non condensing

Reference Materials (available at www.inovonics.com)

EN6091 Gateway Mark II Installation Instructions

EN6091 Gateway Mark II Programming Manual

Inovonics Intrusion System User Manual

Inovonics Intrusion System Brochure

- The range and performance of any wireless product depends on the structure and environment in which it operates.
- Continual enhancements to our products may cause specifications to change without notice.
- Inovonics supports recycling and reuse whenever possible. Please recycle these parts using a certified electronics recycler.

Technical documents

For technical documents visit us at <http://www.inovonics.com/support/tech-documents/> or use the QR code below.



Draft